






2x 110W LED Stage Blinder


The **B Blinded** is the future of all blinders. A powerful blinder with a 2x 110 W warm white LED engine, including tungsten emulation feature. The output can be compared to DWE 2x 650 W but with many extra functionalities. No more dimmers, less cables, but more functions with faster installation and more creativity. Furthermore this versatile fixture is arrayable to make a 4-6 or 8 lite blinder unit up to a 20 lite! Vertical or horizontal it is up to your design!

Physical

| Dimensions (WxHxD) | 400 x 220 x 205 mm | |
|------------------------------|--------------------|--|
| Packiging dimensions (WxHxD) | 510 x 320 x 300 mm | |
| Nett weight | 6,2 kg | |
| Gross weight | 7,2 kg | |




400 mm



Mounting options

| Hanging | Dedicated hanging bracket with M12 mounting holes The mounting options depend on its placement Different jointing options depending on the matrix build up Max load per bracket: 10 units |
|------------------------------|--|
| Standing | On chassis |
| 2nd suspension / safety wire | Different possibilities (depending on the mounting options) Eye bolt for carabiner |
| | |



Bedrijvenpark De Veert 13/004 B-2830 Willebroek Belgium www.luxibel.com All specifications are subjected to change without prior notice.





SPEC SHEET

Control


| Menu control via LED display with 4 buttons | | In/ Link | XLR 5 pin |
|---|---------------------------|----------|---------------------------|
| Control | DMX512, manual | DMX mode | 1/2/4/6/8 channels |
| Dimmer mode | 0 ~100% - 8 or 16bit mode | Strobe | Adjustable speed + random |

| Optical | | |
|--------------------|---|---|
| LED sources | CREE LED | Photometrics Diagram |
| Beam angle | 50° | Distance (m) 0 2 4 6 8 |
| Light output | 3465 lux @ 2m 915 lux @ 4m 457 lux @ 6m | bijued o 1,8 m 3,6 m 5,4 m 7,2 m 50° |
| CRI | 81,9 CRI | |
| Colour temperature | 2.700K - 1200K in Tungsten mode | lux (WW2) 3465 915 457 260 |
| Tungsten mode | Amber is mixed at low light levels | |
| Colours | Warm white + Amber | |
| Dim speed | Fast, smooth or under | |

| Electrical | | | |
|---------------------|---------------------|-------------|--|
| Fixture rated power | 235W | Input power | 100 - 240V ~ 50/60Hz - Auto switching power supply |
| LED engine | 2x 125W flickerfree | In/Link | PowerCON TRUE1 - max link current 10A |
| Refresh rate | 1200hz | | |

Connectivity

- 1 Display with menu control button
- 2 DMX and power control LED
- 3 DMX input
- 4 DMX output
- 5 Power input
- 6 Power output
- 7 Secondary suspension



| Accessories | | Environmental | |
|--------------------------|---------------------|---------------|----------------------------|
| Included | Optional | IP Rating | IPx4 |
| 1x Powercable | Big Hanging Bracket | Cooling | Very low noise level |
| 1x Hanging bracket | | | Temperature controlled fan |
| 4x Mounting pins on wire | | | |

Bedrijvenpark De Veert 13/004 B-2830 Willebroek Belgium www.luxibel.com All specifications are subjected to change without prior notice.