

Technical Datasheet

tasker® C285 – 1x0,50 mm² RoHS₃

Guitar Cable with Carbon Screen



| | | | | |
|---|---|---|---|---|
| A | B | C | D | E |
|---|---|---|---|---|

CATEGORY Guitar Cable (See Audio Catalogue)

APPLICATIONS Premade cables for instrumental cable like Guitar, Bass and Keyboards

- A:** Soft Black PVC. Outer cable Diam. Ø 6,20 ± (0,20) mm.
- B:** First shielding with O.F.C. red copper Spiral covering 100%.
- C:** Second shielding with conductive carbon screen.
- D:** Transparent PPE insulation with outside diameter Ø: 1,70 ± (0,20) mm.
- E:** O.F.C. stranded tinned copper formation 7x0,30 mm.
Nom. Cross section 1x 0,50 mm².

MARKING tasker® C285 1x0,50 PROFESSIONAL NOISELESS GUITAR CABLE LOW CAPACITY

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

| | |
|-----------------------|-----------|
| Conductor Resistance | 38 Ω/km |
| Capacity Core/Shield | 110 pF/m |
| Max Rated Voltage | 49 V |
| Operative Temperature | -15/+70°C |

| | | | | | | | | | | |
|---------|---|-----------------------|-------------------|--------------|---|----------------------|------------------|--------------|---|-------------------|
| USE | X | Indoor | Interno Edificio | INSTALLATION | X | Fixed | Fissa | INFORMATION | X | RoHS2 Compliant |
| Impiego | | Outdoor Limited | Esterno Limitato | Posa | X | Restricted Mobile | Mobile Limitata | Informazioni | X | Ver. A / 16.05.16 |
| | | Outdoor | Esterno | | | Mobile | Mobile | | | |
| | | Outdoor Direct Burial | Esterno Interrato | | | Mobile in Drag Chain | Mobile in Catena | | | |