

Specifications

Audio and Video		
Inputs	Transmitter: 2x HDMI IN, 1x USB Host (Type-B) Receiver: 1x UTP Input (RJ45)	
Outputs	Transmitter: 1x UTP out (RJ45) Receiver: 2x HDMI OUT, 4x USB 2.0 Type-A out	
Supported Standards	HDMI 1.4	
EDID	Fixed 1080p60	
Data Rate	HDMI: 4.455Gbps USB: 480Mbps	
Transmission Distance	Supported USB Devices	Range
	USB-HID Device	Up to 263ft (80m)
	USB 2.0 Storage Device	Up to 197ft (60m)
Power		
Power Supply	DC 12V	
PoC	One-way PoC supporting, Rx -> Tx	
Environmental		
Operating Temperature	0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing	
Storage Temperature	-20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensing	
Dimensions and Weight		
Height	25mm/0.98in	
Width	215mm/8.46in	
Depth	120mm/4.72in	
Regulatory		
Safety and Emission	CE FCC RoHS RCM EAC UKCA	

Note: WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.

Warranty Information

WyreStorm Technologies ProAV Corporation warrants that its products to be free from defects in material and workmanship under normal use for a period of five (5) years from the date of purchase. Refer to the Product Warranty page on wyrestorm.com for more details on our limited product warranty.

